

# FSP Series

## FEATURES

- Mild steel construction
- 5mm thick deck plate with checkered safety tread
- Steel grid channel frame
- Painted mild steel
- Pre-corner error adjustment
- Threaded eyebolt holes for easy lifting (eyebolts included)
- Installed with:
  - \* 4 high accuracy IP67 alloy steel shear beam load cells (563YH) (OIML MAA C6, Y=8,500 and NTEP 1:5000 Class III, Multiple Cell)
  - \* 4 swivel mild steel feet with removable rubber base (AMF - 1/2)
  - \* 1 IP67 aluminum 4-way junction box (J04EA)
  - \* 2 eyebolts
  - \* Level bubble
- Measurement Canada approved: NTEP approved:
  - 3'X3', 5Klb - 3'X3', 5Klb
  - 3'X4', 5Klb - 4'X4', 5Klb
  - 4'X4', 5Klb - 4'X4', 10Klb
  - 5'X5', 5Klb



Part#	FSP5X5-5Klb	FSP5X5-10Klb
<b>Capacity</b>	5000 lb	10000 lb
<b>Division</b>	1 lb	2 lb
<b>Platform Size</b>	59 in X 59 in / 150 cm X 150 cm	59 in X 59 in / 150 cm X 150 cm
<b>Platform Material</b>	Mild Steel	Mild Steel
<b>Net Weight</b>	357 lb / 162kg	357 lb / 162kg
<b>Operating Temp.</b>	0 - 40°C / 32 - 104 °F	0 - 40°C / 32 - 104 °F

Part#	FSP3X3-1Klb	FSP3X3-2Klb	FSP3X3-5Klb	FSP4X4-5Klb	FSP4X4-10Klb
<b>Capacity</b>	1000 lb	2000 lb	5000 lb	5000 lb	10000 lb
<b>Division</b>	0.2 lb	0.5 lb	1 lb	1 lb	2 lb
<b>Platform Size</b>	36 in X 36 in / 91.4 cm X 91.4 cm	36 in X 36 in / 91.4 cm X 91.4 cm	36 in X 36 in / 91.4 cm X 91.4 cm	48 in X 48 in / 121.9 cm X 121.9 cm	48 in X 48 in / 121.9 cm X 121.9 cm
<b>Platform Material</b>	Mild Steel	Mild Steel	Mild Steel	Mild Steel	Mild Steel
<b>Net Weight</b>	203 lb / 92kg	203 lb / 92kg	203 lb / 92kg	265 lb / 120kg	265 lb / 120kg
<b>Operating Temp.</b>	0 - 40°C / 32 - 104 °F	0 - 40°C / 32 - 104 °F	0 - 40°C / 32 - 104 °F	0 - 40°C / 32 - 104 °F	0 - 40°C / 32 - 104 °F

\*Dimensions and specifications are subject to change without notice.